
新生命教育協會平安福音中學 NLSI PEACE EVANGELICAL SECONDARY SCHOOL

Solar Control Film – Test Report

Prepared by Suntint Ltd, 2013


Date: 22 Jan 2013

Solar Control Film:





Location of window / Time of daily sunlight



1. Location of window

(1-6/F – Special Rooms)



| Location | Width" | Height" | Unit | Area (Sq) | Direction |
|---------------------|--------|---------|------|-----------|-----------|
| 1-6/F Special Rooms | 125 | 60 | 42 | 2188 | EAST |

2. Location of window

(G-7/F – Main Classrooms)



| Location | Width" | Height" | Unit | Area (Sq) | Direction |
|-----------------------|--------|---------|------|-----------|-----------|
| G-7/F Main Classrooms | 125 | 60 | 106 | 5521 | WEST |

Summary


| Direction Window Area EAST 2,188 Sqft WEST 5,521 Sqft Total Area 7,709 Sqft | | |
|--|------------|-------------|
| WEST 5,521 Sqft | Direction | Window Area |
| | EAST | 2,188 Sqft |
| Total Area 7,709 Sqft | WEST | 5,521 Sqft |
| | Total Area | 7,709 Sqft |
| | | |

On-site Test Location

(3/F Main Classrooms - WEST)




Solar Heat Gain



Solar Heat Gain




Solar Heat Test: Before VS After Solar Film install




BTU


Solar Control Film – Test Report (continue...)

Solar Heat Test: Before VS After Solar Film install



Solar Heat Test: Before VS After Solar Film install





Total Energy Rejected:

69.1%

Energy Saving Analysis

| WINDOW FILM (Spec.) | | CXP-80 |
|-----------------------------|----------------------|---------|
| Performance Results | (%) | CAI -00 |
| Solar Energy | Transmittance | 7 |
| | Absorptance | |
| | Reflectance | |
| √isible Light | Transmittance | 80 |
| | Reflectance (Ex/Int) | 7 |
| JV Rejected | | 99 |
| Shading Coefficient | | |
| J-value | | |
| Total Solar Energy Rejected | | >44 |
| Thickness | | 1.5Mil |
| Tensile Strength (kg/cmSq) | | 2000 |

Solar Control Film – Test Report (continue...)

Calculation on the Energy saving

INIDITY WITHOUT ON MA

| INPUT WITHOUT FILIN | Clear Glass - existing | | |
|--------------------------------|------------------------|-----------|--|
| | | | REMARK |
| Area of Glass (in square feet) | 玻璃窗面積 (平方公) | 7,704 | |
| Solar Load (Btu's/Hr/Sq. Ft) | | 94 | Sunlight pass through window (See picture) |
| Heat Gain or Q (btu's /hour) = | | 724,176 | |
| Total Daily Solar Load = (btu) | | 3,620,880 | Daily 5hrs Solar heat gain |

AC Tonnage Required, Daily = 302 a

INPUT WITH FILM

Glass installed with film

| Area of Glass in square feet Solar Load (Btu's/Hr/Sq. Ft) Heat Gain or Q (btu's /hour) = | 玻璃窗面積(平方公) | 7,704 29 223,416 | Sunlight pass through window (See picture) |
|--|------------|------------------------|--|
| Total Daily Solar Load = (btu) AC Tonnage Required, Daily = | | 1,117,080 93 | Daily 5hrs Solar heat gain |

Solar Control Film – Test Report (continue...)

| avings in AC Tonnage = 20 | |
|--|----------------------------|
| | 209 <mark>a-1</mark> |
| ull-Load Efficiency (kW/Ton), Small Unit 0.8 | .80 <mark>c</mark> |
| WH CHARGE 每度收費 HK\$ 1. | 167 <mark>(8</mark> 1.2 |
| | 25 |
| otal Monthly Savings with Film 每月節省電費 \$ 5,00 | 8 |
| nnual Saving 每年節省電費 8 months of year using air- (每年以 8 個月 HK\$40,06 on) 用冷氣計算) | 31 |
| | |
| RICE (Standard) per Sq Ft HKD 6 | |
| iscounted Price 38.0 | |
| 292,75 | S 500 |
| imple Payback Period (Yr) 回本期(年) 7. | . .3 |
| /arranty (Yr) | 10 |

由於上述結果只採用冬天實況數據綜合分析,因此,如按照春、夏、秋、冬的實際情況每月紀錄,「每年節省電費」的金額將會更高、「回本期」亦會更短。

The information contained in this document is proprietary to Suntint Limited and is tendered for purposes of review and evaluation only. This document shall not be reproduced, in whole or in part, nor shall the information contained herein be used by or disclosed to others except as expressly authorized by Solcon Limited.